



FCC 47 CFR MPE REPORT

TCL OVERSEAS MARKETING LTD

Wireless Subwoofer

Model Number: S55H-SW

Additional Model:

S50H-SW,S58H-SW,S59H-SW,S5****-SW,F30C-SW,F35C-SW,
F38C-SW,F30D-SW,F35D-SW,F38D-SW,F3***-SW,S55H5-SW

(*can be any numerica number"0~9" or alphebtlcal number "A~Z")

FCC ID: 2BEHES55HSW

| | |
|--------------------------|--|
| Applicant: | TCL OVERSEAS MARKETING LTD |
| Address: | 5/F, Building 22E, 22 Science Park East Avenue HongKong Science Park Shatin Hong Kong |
| | |
| Prepared By: | EST Technology Co., Ltd. |
| | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 | |

| | |
|-----------------|------------------|
| Report Number: | ESTE-R2401402-1 |
| Date of Test: | Jan. 05~25, 2024 |
| Date of Report: | Mar. 31, 2025 |

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-10000 | | | 5 | 6 |

(b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-10000 | | | 1.0 | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) |
|--------|-----------------|-------------------------|------------------------|
| SRD 1M | 2402 | 6.54 | 4.5082 |
| | 2440 | 6.14 | 4.1115 |
| | 2480 | 5.76 | 3.7670 |
| SRD 2M | 2402 | 6.53 | 4.4978 |
| | 2440 | 6.09 | 4.0644 |
| | 2480 | 5.74 | 3.7497 |

3. Calculated Result and Limit

| Mode | Peak output power (dBm) | Target power (dBm) | MAX Target power (dBm) | Antenna gain | | Power Density (S) (mW /cm ²) | Limited of Power Density (S) (mW /cm ²) | Test Result |
|-----------|-------------------------|--------------------|------------------------|--------------|----------|--|---|-------------|
| | | | | (dBi) | (Linear) | | | |
| 2.4G Band | | | | | | | | |
| SRD 1M | 6.54 | 1.69 | 8.23 | 8±1 | 9 | 0.0079 | 2.676 | Complies |
| SRD 2M | 6.53 | 1.69 | 8.22 | 8±1 | 9 | 0.0079 | 2.676 | Complies |

End of Test Report